

NEW **DRIADE 230Vac**IP65 IK07 CE 

TIPOLOGIA / TYPOLOGY



Paletto | Bollard

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra | Ground mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor

DRIADE S**DRIADE S-S** H 400 mm**9W** kg 1,1**DRIADE S-M** H 800 mm**9W** kg 1,3

NEW **DRIADE 230Vac**IP65 IK07 CE 

TIPOLOGIA / TYPOLOGY



Paletto | Bollard

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra | Ground mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor

DRIADE M**DRIADE M-S**  H 400 mm**12W** kg 1,40**DRIADE M-M**  H 800 mm**12W** kg 1,60

NEW DRIADE 230Vac

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	S version: 9W M version: 12W
ALIMENTAZIONE POWER SUPPLY	230Vac
ALIMENTATORE POWER SUPPLY UNIT	Integrato (con elettronica 230Vac) <i>Integrated (with 230Vac electronic)</i>
COLLEGAMENTO CONNECTION	Tensione di rete <i>Mains voltage</i>

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2700K, 3000K, 4000K
INDICE RESA CROMATICA CRI CRI	>80 (2700K, 3000K, 4000K)
BINNING	3 step MacAdam <i>3 MacAdam steps</i>
OTTICHE OPTICS	Diffused
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	S version: 9W 896lm M version: 12W 1156lm
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES


PESO WEIGHT	S-S version: kg 1,1 S-M version: kg 1,3 M-S version: kg 1,4 M-M version: kg 1,6
FINITURE FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Antracite txt, Sand <i>txt White, txt Grey, txt Black, Corten, txt Anthracite, Sand</i>
INSTALLAZIONE INSTALLATION	A terra con basetta, viti (incluse) e cassaforma (non inclusa) <i>On ground with base, set screws (included) and housing box (not included)</i>
MATERIALE MATERIAL	Corpo, basetta e stelo in alluminio anticorrosivo, diffusore in PMMA satinato <i>Anticorrosive aluminium body, base and stem, satinized PMMA diffuser</i>

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK07
GLOW WIRE TEST GLOW WIRE TEST	960°C.
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	I
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	I
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

NEW **DRIADE 230Vac**

ACCESSORI | ACCESSORIES

CODICE / CODE	CAE60
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,28
MATERIALE MATERIAL	Polietilene Polyethylene

