

NEW GEA FRAME IP65 - XXS C.C.

IP65 IK06 CE   

TIPOLOGIA / TYPOLOGY


Incasso | Recessed

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A soffitto | Ceiling mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



GEA FRAME IP65 - XXS

1W - 1,6W

 kg 0,03 21 mm

NEW GEA FRAME IP65 - XXS C.C.

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	1W - 1,6W
ALIMENTAZIONE POWER SUPPLY	C.C.
ALIMENTATORE POWER SUPPLY UNIT	1W - 350mA Non incluso Not included 1,6W - 500mA Non incluso Not included
COLLEGAMENTO CONNECTION	Serie Series

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	18°, 35°, 57°
UGR	<19
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	1W 85lm 35° 1,6W 126lm 35°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	Kg 0,03
FINITURE FINISHES	Bianco txt , Grigio txt, Nero txt txt White, txt Grey, txt Black
INSTALLAZIONE INSTALLATION	A incasso su cartongesso o legno tramite molla (non incluse), a incasso su muratura per interferenza tramite o-ring (incluso) e cassaforma (non inclusa) Recessed on plasterboard or wood with springs (not included), recessed on brickwork through o-ring (included) and housing, box (not included)
MATERIALE MATERIAL	Corpo in alluminio anticorrosivo, dissipatore in alluminio anticorrosivo, lenti in PMMA o diffusore in PMMA opalino Anticorrosive aluminium body, anticorrosive aluminium heatsink, PMMA lens or Opal PMMA diffuser


CARATTERISTICHE GENERALI | GENERAL FEATURES


TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK06
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	50° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	/
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1


NEW

GEA FRAME IP65 - XXS C.C.

ACCESSORI | ACCESSORIES

CODICE / CODE	ML021	
TIPOLOGIA / TYPOLOGY	Molla di torsione <i>Torsion spring</i>	 kg 0,001
MATERIALE MATERIAL	Acciaio inox <i>Stainless steel</i>	



CODICE / CODE	CAS20	
TIPOLOGIA / TYPOLOGY	Cassaforma <i>Housing box</i>	 kg 0,01
MATERIALE MATERIAL	PVC	

