

NEW LICO BOLLARD S-L 24Vdc

IP65 IK07 CE   

TIPOLOGIA / TYPOLOGY


Paletto | Bollard

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra | Ground mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



LICO BOLLARD S-L

 H 700 mm

3,5W



kg 0,54

NEW LICO BOLLARD S-L 24Vdc

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	3,5W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	3,5W - 24Vdc (Non incluso Not included)
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2700K, 3000K, 4000K
INDICE RESA CROMATICA CRI CRI	>80 (2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	ASYM
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	3,5W 170lm
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	kg 0,3
FINITURE FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Antracite txt, Verde, Sand, Bronzo anodico opaco txt White, txt Grey, txt Black, Corten, txt Anthracite, Green, Sand, Anodic bronze matt
INSTALLAZIONE INSTALLATION	A terra con basetta e viti (includere) Ground mounted with base and screws (included)
MATERIALE MATERIAL	Corpo in alluminio anticorrosivo, basetta in acciaio inox AISI 304, vetro temperato serigrafato Anticorrosive aluminium body, AISI 304 stainless steel base, Silk-screen printed tempered glass

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP65
GRADO DI RESISTENZA IMPACT RESISTANCE	IK07
GLOW WIRE TEST GLOW WIRE TEST	960°C.
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	I
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1