


NEW NISO RECESSED L 24VdcIP67 IK09 CE III WP TIPOLOGIA / *TPOLOGY***Incasso** | *Recessed*POSIZIONE INSTALLATIVA | *INSTALLATION POSITION***A terra** | *On ground*AMBIENTE INSTALLATIVO | *INSTALLATION LOCATION***Esterno** | *Outdoor*

NISO RECESSED - L

31W kg 1,35

NEW NISO RECESSED L 24Vdc

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	31W
ALIMENTAZIONE POWER SUPPLY	24Vdc
ALIMENTATORE POWER SUPPLY UNIT	31W - 24Vdc (Non incluso Not included)
COLLEGAMENTO CONNECTION	Parallelo Parallel

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 McAdam step
OTTICHE OPTICS	9°, 13°, 30°, 40°, ASYM, 20°x40°, 60°
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	31W 2746lm 30°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO WEIGHT	kg 1,35
FINITURE FINISHES	Acciaio, Acciaio Spazzolato Steel, Brushed Steel
INSTALLAZIONE INSTALLATION	A incasso a terra con cassaforma (non inclusa), viti autofilettanti (incluse) Recessed on ground with housing box (not included), self-tapping screws (included)
MATERIALE MATERIAL	Corpo in alluminio anticorrosivo, ghiera in acciaio Inox AISI 316L, vetro temperato trasparente Anticorrosive aluminium body, AISI 316L stainless trim, transparent tempered glass


CARATTERISTICHE GENERALI | GENERAL FEATURES


TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP67
GRADO DI RESISTENZA IMPACT RESISTANCE	IK09
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	Si / Yes
CARRABILE DRIVE OVER	2000 Kg
SICUREZZA STANDARD STANDARD SAFETY	WP System
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

NEW

NISO RECESSED L 24Vdc

ACCESSORI | ACCESSORIES

CODICE / CODE	CA135
TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,31
MATERIALE MATERIAL	Polipropilene Polypropylene



FILTRI | FILTER

CODICE / CODE	HC
TIPOLOGIA / TYPOLOGY	Filtro Honeycomb Honeycomb filter

