

## NEW UDEO CEILING 24Vdc

IP65 IK06 CE     

TIPOLOGIA / TYPOLOGY


Plafone | Ceiling mounting

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A plafone | Ceiling mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



UDEO CEILING

**9,5W**

kg 0,43

# NEW UDEO CEILING 24Vdc

## CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA   POWER CONSUMPTION	9,5W
ALIMENTAZIONE   POWER SUPPLY	24Vdc
ALIMENTATORE   POWER SUPPLY UNIT	9,5W - 24Vdc non incluso   Not included
COLLEGAMENTO   CONNECTION	Parallelo   Parallel

## CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED   LED COLOUR	2200K, 2700K, 3000K, 4000K, Red, Green, Blue
INDICE RESA CROMATICA CRI   CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 step MacAdam   3 MacAdam steps
OTTICHE   OPTICS	25°, 36°, 62°, Diffused
UGR	<19
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	9,5W 771lm 36°
DURATA MEDIA LED   AVERAGE LED LIFE	50.000h L80 B10

## CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES

PESO   WEIGHT	Kg 0,43
FINITURE   FINISHES	Bianco txt, Grigio txt, Nero txt, Corten, Antracite txt, Verde, Sand txt White, txt Grey, txt Black, Corten, txt Anthracite, Green, Sand
INSTALLAZIONE   INSTALLATION	A plafone tramite basetta di fissaggio (inclusa) e viti (non incluse) Ceiling mounting with mounted base (included) and set screws (not included)
MATERIALE   MATERIAL	Corpo in alluminio, vetro temperato serigrafato Aluminium body, silk-screen printed tempered glass

## CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE   INGRESS PROTECTION	IP65
GRADO DI RESISTENZA   IMPACT RESISTANCE	IK06
GLOW WIRE TEST   GLOW WIRE TEST	960°C.
TEMPERATURA MASSIMA APPARECCHIO MAX. TEMPERATURE OF FIXTURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO   APPLIANCE CLASS	III
CALPESTABILE   WALKOVER	No
CARRABILE   DRIVE OVER	No
SICUREZZA STANDARD   STANDARD SAFETY	I
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

LLD

**NEW** UDEO CEILING 24Vdc

FILTRI | FILTER

<b>CODICE / CODE</b>	<b>HC</b>
<b>TIPOLOGIA / TYPOLOGY</b>	<b>Filtro Honeycomb</b> <i>Honeycomb filter</i>
<b>NOTE</b>	<i>with 25°, 36°, 62° lens only</i>

