

IP54 IK08 CE   | 

TIPOLOGIA / TYPOLOGY


Incasso | Recessed

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A soffitto | Ceiling mounting

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION

Esterno | Outdoor



ZEFIRO S


1W



kg 0,03



16 mm



ZEFIRO M

1W - 1,6W - 2,5W



4W - 8W



kg 0,05



26mm

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	S version: 1W M standard version: 1W - 1,6W - 2,5W RGBW-TW version: 4W
ALIMENTAZIONE POWER SUPPLY	C.C.
ALIMENTATORE POWER SUPPLY UNIT	1W - 350mA (non incluso not included) — S version 1W - 350mA (non incluso not included) 1,6W - 500mA (non incluso not included) 2,5W - 700mA (non incluso not included) } M version 4W - 350mA (con centralina non inclusa with control unit not included) – M RGBW
COLLEGAMENTO CONNECTION	Serie Series

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	S version: 2200K, 2700K, 3000K, 4000K, Red, Green, Blue M version: 2200K, 2700K, 3000K, 4000K, Red, Green, Blue, RGBW, T.White
INDICE RESA CROMATICA CRI CRI	>80 (2200K, 2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	Diffused
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	S version: 1W 55lm M version: 1W 46lm - 1,6W 65lm - 2,5W 91lm
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES













PESO WEIGHT	S version: kg 0,03 - M version: kg 0,05
FINITURE FINISHES	PMMA opalino <i>Opal PMMA</i>
INSTALLAZIONE INSTALLATION	A incasso su cartongesso o legno tramite molla (non inclusa), a muratura con cassaforma (non inclusa) <i>Recessed on plasterboard or wood with spring (not included), recessed on brickwork with housing box (not included)</i>
MATERIALE MATERIAL	Corpo in alluminio anticorrosivo, diffusore in PMMA satinato <i>Anticorrosive aluminium body, satinized PMMA diffuser</i>

CARATTERISTICHE GENERALI | GENERAL FEATURES

TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP54
GRADO DI RESISTENZA IMPACT RESISTANCE	IK08
GLOW WIRE TEST GLOW WIRE TEST	960°C.
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	III
CALPESTABILE WALKOVER	No
CARRABILE DRIVE OVER	No
SICUREZZA STANDARD STANDARD SAFETY	I
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1

ZEFIRO

ACCESSORI | ACCESSORIES

S version	CODICE / CODE	ML016		
	TIPOLOGIA / TYPOLOGY	Molla di torsione <i>Torsion spring</i>	 kg 0,001	
	MATERIALE / MATERIAL	Acciaio inox <i>Stainless steel</i>		
M version	CODICE / CODE	CAE16		
	TIPOLOGIA / TYPOLOGY	Cassaforma <i>Housing box</i>	 kg 0,01	
	MATERIALE / MATERIAL	Polipropilene <i>Prolypropylene</i>		
M version	CODICE / CODE	ML025		
	TIPOLOGIA / TYPOLOGY	Molla di torsione <i>Torsion spring</i>	 kg 0,001	
	MATERIALE / MATERIAL	Acciaio inox <i>Stainless steel</i>		
M version	CODICE / CODE	CAE25		
	TIPOLOGIA / TYPOLOGY	Cassaforma <i>Housing box</i>	 kg 0,012	
	MATERIALE / MATERIAL	PVC		