

ZELOS S-M-L 230Vac

IP67 IK09 CE       | A > A+ > A++

TIPOLOGIA / TYPOLOGY


Incasso | Recessed

POSIZIONE INSTALLATIVA | INSTALLATION POSITION

A terra | On ground

AMBIENTE INSTALLATIVO | INSTALLATION LOCATION


Esterno | Outdoor



ZELOS S

14W


 kg 1,40



ZELOS M


19W

 kg 1,68



ZELOS L

25W

 kg 1,87

ZELOS S-M-L 230Vac

CARATTERISTICHE ELETTRICHE | ELECTRICAL FEATURES

POTENZA ASSORBITA POWER CONSUMPTION	S version: 14W - M Version: 19W - L version: 25W
ALIMENTAZIONE POWER SUPPLY	230Vac
FREQUENZA FREQUENCY	50/60 Hz
ALIMENTATORE POWER SUPPLY UNIT	Integrato (con elettronica 230Vac) Integrated (with 230Vac electronic)
COLLEGAMENTO CONNECTION	Tensione di rete Mains voltage

CARATTERISTICHE ILLUMINOTECNICHE | LIGHTING FEATURES

COLORE LED LED COLOUR	2700K, 3000K, 4000K
INDICE RESA CROMATICA CRI CRI	>80 (2700K, 3000K, 4000K)
BINNING	3 step MacAdam 3 MacAdam steps
OTTICHE OPTICS	12°, 24°, 38°
FLUSSO REALE EMESSO - 3000K REAL OUTPUT FLUX	S version: 14W 1174lm 24° M version: 19W 1633lm 24° L version: 25W 2056lm 24°
DURATA MEDIA LED AVERAGE LED LIFE	50.000h L80 B10

CARATTERISTICHE MECCANICHE | MECHANICAL FEATURES


PESO WEIGHT	S version: kg 1,40 M Version: kg 1,68 L version: kg 1,87
FINITURE FINISHES	Acciaio, Acciaio Spazzolato <i>Steel, Brushed Steel</i>
INSTALLAZIONE INSTALLATION	A incasso a terra con cassaforma (non inclusa), viti autofilettanti (incluse) <i>Recessed on ground with housing box (not included), self-tapping, screws (included)</i>
MATERIALE MATERIAL	Corpo in alluminio anodizzato, ghiera in acciaio Inox AISI 316L, vetro temperato trasparente <i>Anticorodal aluminium body, AISI 316L stainless trim, transparent tempered glass</i>


CARATTERISTICHE GENERALI | GENERAL FEATURES


TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-10°C +45°C
GRADO DI PROTEZIONE INGRESS PROTECTION	IP67
GRADO DI RESISTENZA IMPACT RESISTANCE	IK09
GLOW WIRE TEST GLOW WIRE TEST	960°C
TEMPERATURA SCHERMO SCREEN TEMPERATURE	40° @ Ta = 25°
CLASSE DI ISOLAMENTO APPLIANCE CLASS	I
CALPESTABILE WALKOVER	Sì / Yes
CARRABILE DRIVE OVER	2000 Kg
SICUREZZA STANDARD STANDARD SAFETY	WP System
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	GR1



ZELOS S-M-L 230Vac

ACCESSORI | ACCESSORIES

S version	CODICE / CODE	CC110
	TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,31
	MATERIALE / MATERIAL	Polietilene Polyethylene



M and L versions	CODICE / CODE	CL110
	TIPOLOGIA / TYPOLOGY	Cassaforma Housing box  kg 0,61
	MATERIALE / MATERIAL	Polietilene Polyethylene



FILTRI | FILTER

CODICE / CODE	HC
TIPOLOGIA / TYPOLOGY	Filtro Honeycomb Honeycomb filter

